

Classe H2 Spartitraffico - Barriera 3 onde W6


Class H2 Central reserve - 3-waves guardrail W6

Aufhaltestufe H2 Mittelstreifenbereich - 3-welliges Rückhaltesystem W6

Classe H2 Glissière centrale - Glissière 3 crosses simple W6

Clase H2 Paso de mediana - Barrera de triple onda simple W6

CE n. AISICO
028/CPD/2010




Caratteristiche Characteristics, Eigenschaften, Caractéristiques, Características

Altezza fuori terra Height above ground level, Höhe über Grundboden, Hauteur hors sol, Altura sobre el suelo	900 ± 50 mm
Profondità d'infissione Depth of penetration, Rammtiefe, Profondeur de piling du poteau, Longitud hincada	750 mm
Ingombro trasversale Overall width, Gesamtbreite, Grosseur hors tout, Anchura total	875 mm
Interasse pali Post spacing, Steherabstand, Distance entre poteaux, Distancia entre postes	1500 mm

Rapporti di prova Crash test reports, Testberichte, Comptes rendus d'essais, Relaciones de pruebas

Test n.	Facility	Test	Type	Barrier length m	Mass kg	Speed km/h	ASI max 1.4	THIV max 33 km/h	D m	Vi m	W m
PROVA 646	Aisico	TB51	Laterale 20°	99	16.000	70			1,8	1,9	2,1=W6
PROVA 647	Aisico	TB11	Laterale 20°	99	900	100	0,7=A	20	0,5		1,2=W4



Componenti Components, Bauteile, Composants, Elementos

	Descrizione Description		Materiale Material	Codice Code
13	Bullone completo Bolt with nut and washer, Schraube komplett, Boulon complet, Tornillo completo con tuerca y arandela	M16x50 mm	Classe 8.8	63800014
14		M16x30 mm	Classe 8.8	63800012
11	Piastrina copriasola Slot covering plate, Lochabdeckplatte, Plaque de couverture fente, Placa cubre-ranura	100x40x4 mm	S 275 JR	59600127
711	Distanziatore romboidale Rhomboidal spacer, Rhomboidisch. Abstandhalter, Entretroise en losange, Separador romboidal	Th=5 mm	S 235 JR	59601255
712	Palo "C" C-post, C-Steher, Poteau en C, Poste "C"	120x80x30 Th=5 H=1580 mm	S 235 JR	59400483
415	Fascia 3 onde 3-waves beam, 3-wellige Leitschiene, Glissière 3 crosses, Banda triple onda	L=4816 (1500x3) Th=2,5 mm	S 235 JR	59300177