


## Classe H2 Spartitraffico - Barriera 2 onde W4

Class H2 Central reserve - 2-waves guardrail W4

Aufhaltestufe H2 Mittelstreifenbereich - 2-welliges Rückhaltesystem W4

Classe H2 Glissière centrale - Glissière 2 crosses simple W4

Clase H2 Paso de mediana - Barrera de doble onda simple W4





### Caratteristiche Characteristics, Eigenschaften, Caractéristiques, Características

<b>Altezza fuori terra</b> Height above ground level, Höhe über Grundboden, Hauteur hors sol, Altura sobre el suelo	850 ± 30 mm
<b>Profondità d'infissione</b> Depth of penetration, Rammtiefe, Profondeur de piling du poteau, Longitud hincada	900 mm
<b>Ingombro trasversale</b> Overall width, Gesamtbreite, Grosseur hors tout, Anchura total	291 mm
<b>Interasse pali</b> Post spacing, Steherabstand, Distance entre poteaux, Distancia entre postes	1500 mm

### Rapporti di prova Crash test reports, Testberichte, Comptes rendus d'essais, Relaciones de pruebas

Test n.	Facility	Test	Type	Mass kg	Speed km/h	ASI max 1.4	PHD* max 20 g	THIV max 33 km/h	D m	Vi m	W m
PROVA 954	Aisico	TB51	Laterale 20°	13000 (bus)	70	-	-	-	1,2	2,5=Vi7	1,3=W4
PROVA 960	Aisico	TB11	Laterale 20°	900 (car)	100	A	-	33	0,3	-	0,6=W1



#### Componenti Components, Bauteile, Composants, Elementos

	Descrizione Description		Materiale Material	Codice Code
5	<b>Bullone completo</b> Bolt with nut and washer, Schraube komplett, Boulon complet, Tornillo completo con tuerca y arandela	M12x50 mm	Classe 8.8	<b>63800857</b>
4		M16x30 mm	Classe 8.8	<b>63800012</b>
3	<b>Piastrina copriasola</b> Slot covering plate, Lochabdeckplatte, Plaque de couverture fente, Placa cubre-ranura	100x40x4 mm	S 275 JR	<b>59600127</b>
2	<b>Palo "C"</b> C-post, C-Steher, Poteau en C, Poste "C"	120x55x30 Th=4 L=1700 mm	S 275 JR	<b>59400943</b>
1	<b>Fascia 2 onde</b> 2-waves beam, 2-wellige Leitschiene, Glissière 2 crosses, Banda doble onda	L=4816 (1500x3) Th=2,85 mm	S 355 JR	<b>59300504</b>