

Classe H3 Bordo Laterale - Barriera 3 onde singola su rilevato W5



Class H3 Roadside - 3-waves single sided guardrail W5

Aufhaltestufe H3 für rammfähige Böden - 3-welliges Rückhaltesystem W5

Classe H3 Bord latéral - Glissière 3 crosses simple sur remblai W5

Clase H3 Borda lateral - Barrera de triple onda simple sobre base terreno W5

CE n. AISICO
243/2131/CPD/2012





Caratteristiche Characteristics, Eigenschaften, Caractéristiques, Características

Altezza fuori terra Height above ground level, Höhe über Grundboden, Hauteur hors sol, Altura sobre el suelo	1195 ± 50 mm
Profondità d'infissione Depth of penetration, Rammtiefe, Profondeur de piling du poteau, Longitud hincada	900 mm
Ingombro trasversale Overall width, Gesamtbreite, Grosseur hors tout, Anchura total	565 mm
Interasse pali Post spacing, Steherabstand, Distance entre poteaux, Distancia entre postes	1500 mm

Rapporti di prova Crash test reports, Testberichte, Comptes rendus d'essais, Relaciones de pruebas

Test n.	Facility	Test	Type	Barrier length m	Mass kg	Speed km/h	ASI max 1.4	THIV max 33 km/h	D m	Vi m	W m
PROVA 360	Aisico	TB61	Laterale 20°	90	16.000	80			1,4	2	1,6=W5
PROVA 380	Aisico	TB11	Laterale 20°	90	900	100	1=A	24,6	0,4		1=W3



Componenti Components, Bauteile, Composants, Elementos

	Descrizione Description		Materiale Material	Codice Code
638	Manicotto di giunzione per corrente Coupling box rear reinforcement, Verbindungsmuffe für Längsträger, Jonction poutre, Conector		S 235 JR	59601041
637	Tubo quadro antirotazione Anti-rotation square tube, Anti-Rotations-Vierkantrohr, Tube carré antirotation, Tubo cuadrado anti-rotación	120x120 Th=5 H=120 mm	S 235 JR	59601039
636	Distanziatore trapezoidale inferiore Trapezoidal lower spacer, Unterer trapezförmiger Abstandhalter, Entretoise trapézoïdale inférieure, Separador trapezoidal inferior		S 275 JR	59601037
635	Piastra di chiusura superiore Upper covering plate, Obere Abdeckplatte, Plaque de recouvrement supérieure, Placa de cierre superior		S 235 JR	59601035
634	Distanziatore trapezoidale superiore Trapezoidal upper spacer, Oberer trapezförmiger Abstandhalter, Entretoise trapézoïdale supérieure, Separador trapezoidal superior		S 235 JR	59601032
633	Corrente "U" U-rear reinforcement, U-Längsträger, Poutre en U, Larguero "U"	120x65 Th=3 L=4490 (1500x3) mm	S 235 JR	59500093
632	Palo "C" C-post, C-Steher, Poteau en C, Poste "C"	120x80x30 Th=5 H=2000 mm	S 235 JR	59400448
18	Fascia 3 onde 3-waves beam, 3-wellige Leitschiene, Glissière 3 crosses, Banda triple onda	L=4500 (1500x3) Th=3 mm	S 235 JR	59300079
14	Bullone completo Bolt with nut and washer, Schraube komplett, Boulon complet, Tornillo completo con tuerca y arandela	M16x30 mm	Classe 8.8	63800012
13		M16x50 mm	Classe 8.8	63800014
11	Piastrina copriasola Slot covering plate, Lochabdeckplatte, Plaque de couverture fente, Placa cubre-ranura	100x40x4 mm	S 275 JR	59600127